



Stainless steel membrane Pressure Switch:

- Snap action micro switch with self-cleaning solid silver rivets
- 250V / 4A
- Change over contact SPDT
- Stainless steel membrane material 1.4404
- Switching range: 0,2...20bar
- Max. system pressure 60bar
- Factory Switch Point setting
- Temperature range: -55°C up to +100°C
- E-connection DIN EN 175301-803A incl. socket, alternative plug M12x1 or cable outlet

Order code

FDC - A - BBB - C - DE - F

A	Output	
	1 = SPDT	
	6 = normally open NO	
	7 = normally closed NC	

BBB	Set point	
	factory setting between 0,2...20bar	

C	Membrane	
	S = stainless steel	1.4404

D	Fluid connection material	
	without = zinc plated steel	
	S = Stainless steel 1.4305 / ANSI 303	

E	Fluid connection	
	1 = G1/8"	3 = G1/4"
	D = R1/8"	R = R1/4"
	E = 1/8NPT	6 = 1/4NPT
	T = M10x1 (12,5mm) $\phi=8,0$ with sintered filter	
	U = M10x1 (20mm) $\phi=8,0$ with sintered filter	
	W = M10x1 (12,5mm) $\phi=8,3$ with sintered filter	
	N = M10x1 (20mm) $\phi=8,3$ with sintered filter	

F	Electrical connection	
	1 = DIN EN 175301-803A incl. socket	
	2 = plug M12x1	
	5 = cable output, L=0,5m	

Options

011041	2m cable with socket M12x1
---------------	----------------------------

Order sample: FDC-1-020-S-3-1

Set point: **10 bar**

falling

rising

FDC: Pressure Switch type FDC

6: Output: SPDT

020: Adjustment range: factory setting

S: Membrane: stainless steel

3: Fluid connection: male G1/4"

1: E-connection: DIN EN 175301-803A incl. socket

Set point: 10bar falling

Technical data

Construction:	snap action micro switch SW27
Operating fluid:	compressed air, neutral fluids/gases, most fire extinguisher agents
Mechanical installation:	over fluid connection
Mounting position:	any
Max. system pressure:	60bar
Repeatability:	max. $\pm 2\%$ of full scale at room temperature
Hysteresis:	guide value: 0,1bar + 5...20% of set point, adjustable
Life cycles, mech.:	$> 5 \times 10^4$
Max. switching frequency:	$\sim 1\text{Hz}$
Temperature range:	$-55 \dots +100^\circ\text{C}$
Vibration resistance:	10g (10 ... 2000Hz) sinus acc. to ISO 16750-3
Shock resistance:	30g, 14ms shaped sinus acc. to DIN 40046, T7
Switching element:	snap action micro switch with self cleaning rivets
Contact rivets:	solid silver, optional gold plated
CE-mark:	acc. to EU-standards: 2014/35/EU (LVD), 2011/65/EU (RoHS)
Protection class:	IP65 acc. to DIN EN 60529; IP67 using plug M12x1 or cable outlet
Weight:	$\sim 0,15\text{kg}$

please contact the technical support for alternative or special requirements
Subject to technical alternations!

Electrical connection data – dimensions

M10x1 Sintered filter	DIN EN 175301-803A	Plug M12x1	Cable output																		
	<table border="1"> <thead> <tr> <th>250VAC</th> <th>24VDC</th> </tr> </thead> <tbody> <tr> <td>Ohmic load</td> <td>4A</td> </tr> <tr> <td>Inductive load</td> <td>2A</td> </tr> </tbody> </table>	250VAC	24VDC	Ohmic load	4A	Inductive load	2A	<table border="1"> <thead> <tr> <th>48VAC</th> <th>24VDC</th> </tr> </thead> <tbody> <tr> <td>Ohmic load</td> <td>4A</td> </tr> <tr> <td>Inductive load</td> <td>2A</td> </tr> </tbody> </table>	48VAC	24VDC	Ohmic load	4A	Inductive load	2A	<table border="1"> <thead> <tr> <th>250VAC</th> <th>24VDC</th> </tr> </thead> <tbody> <tr> <td>Ohmic load</td> <td>4A</td> </tr> <tr> <td>Inductive load</td> <td>2A</td> </tr> </tbody> </table>	250VAC	24VDC	Ohmic load	4A	Inductive load	2A
250VAC	24VDC																				
Ohmic load	4A																				
Inductive load	2A																				
48VAC	24VDC																				
Ohmic load	4A																				
Inductive load	2A																				
250VAC	24VDC																				
Ohmic load	4A																				
Inductive load	2A																				